


PISTON SEAL DOUBLE-ACTING PTFE FACE WITH PRE-LOADED O-RING



PISTON SEAL | DOUBLE-ACTING | PTFE FACE WITH PRE-LOADED O-RING


P94

The Hallite P94 is a compact highperformance double-acting piston seal with a proven design pedigree.

The product is a class-leading sealing solution for use in the most demanding applications. The standard P94 seal face employs a trapezoidal cross-section allowing optimal compression and load transfer to the seal face via the rubber energizer whilst being highly responsive to changes in pressure and/or direction of travel.

Uses include demanding, performance-critical applications in construction equipment, machine tools, material handling, agricultural equipment, injection moulding machines and a wide range of other industries.

This seal face is available in a range of materials from the high-performing Armorlene® series including HLX, a proprietary Hallite PTFE formulation which offers outstanding wear and extrusion-resistance properties and suitability in a wide range of operating conditions and fluid media.



FEATURES

- Compact piston seal design
- Superior static and dynamic sealing performance
- No stick-slip, low breakout and low running friction
- Seal ring component can be machined to any size up to 1300mm
- Design enables larger extrusion gap without loss of seal performance

TECHNICAL DETAILS		
OPERATING CONDITIONS	METRIC	INCH
MAXIMUM SPEED	Up to 15m/sec	Up to 50ft/sec
TEMPERATURE RANGE*	-45 to 200°C	-49 to 392°F
MAXIMUM DYNAMIC PRESSURE**	600 bar	8700 psi

^{*}Dependent upon energiser used (NBR, FKM, etc.).

Hallite Seals Australia Ptv. Ltd.

T: +61 (0) 2 8886 1600

Hallite Sealing Solutions (I) Pvt. Ltd.

Special Plot #10, 3rd Main 1st Stage, Peenya Industrial Estate Bangalore 560 058 T: +91 (0)80 2372 6000

Hallite Seals (Canada) Ltd.

5630 Kennedy Road Mississauga Ontario L4Z 2A9 T: +1 (905) 361-2350

ΙΤΔΙΥ

Hallite Italia srl

Via Francia 21

Hallite Shanghai Co. Ltd.

785 Xing Rong Road Jiading Industrial Park Jiading District Shanghai 201807

UNITED KINGDOM

Hallite Seals International Ltd.

GERMANY

Dichtelemente Hallite GmbH

Billwerder Ring 17 T: +49 (0)40 73 47 48-0 F: +49 (0)40 73 47 48 49

LINITED STATES Hallite Seals Americas

50777 Varsity Court

Michigan 48393 T: +1 (248) 668 5200 F: +1 (248) 668 5210

^{**}For pressures above 400 bar (5800 psi), contact Hallite Engineering.